# **SAMS**UNG



## UHD Signage - 98"

QH98C / QM98C / QE98C

## QE98C

## Key features

## QH98C / QM98C



#### Super-sized Screen

Discover the grand viewing experience of through a super-sized display that draws viewers in. The display packs realistic visuals and vibrant colors that are sure to make its contents the focal point of any space.



#### Slim Design

QE98C packs a breathtaking minimalist design with its slim profile and sleek look. It's designed to fit any space harmoniously, and can be seamlessly mounted to a wall as if it's a piece of art.

\* Wall Mount must be purchased separately.



#### Quantum Processor 4K

Intelligent UHD upscaling technology, powered by Samsung's Quantum Processor 4K, elevates lower-resolution video to UHD-level quality, providing professional picture quality.

\* Viewing experience may vary according to types of content and format.



#### Supersized Screen

A 98-inch screen allows you to enjoy a complete view without the distraction of bezels, providing a clean and uncluttered presentation – perfect for both conference rooms and retail environments.

#### Slim Design

The QH98C and QM98C redefine space optimization with its sleek and slim design. Measuring only 48.1mm in depth and weighing 56.3kg, it is the thinnest

98-inch display in its class.

#### Quantum Processor Lite 4K

Intelligent UHD upscaling technology, powered by Samsung's Quantum Processor 4K, elevates lower-resolution video to UHD-level quality, providing professional picture quality.

\* Viewing experience may vary according to types of content and format.



#### SMARTVIEW+

SMARTVIEW+ enables wireless screen sharing for easy collaboration and quick screen switching with just a click.



#### Samsung VXT

Samsung VXT is the cloud-based visual display solution, bringing a content management system and remote signage management together in one secure platform.

\* Samsung VXT must be purchased separately.



#### **ENERGY STAR / EPEAT Bronze**

The QH98C and QM98C series have earned an ENERGY STAR 8.0 certification from the Environmental Protection Agency for its energy efficiency and an Electronic Product Environmental Assessment Tool (EPEAT) certification in recognition of its eco-conscious efforts, such as its recycled plastic use.

## Specifications

$\begin{tabular}{ c                                   $		Model		QH98C	QM98C	QE98C
Panel Product Probability Probability Probability Probability   0 Image: Probability Image: Probability Image: Probability Image: Probability Image: Probability		Diagonal Sizo	Class	98	98	98
Panel Instrument length (P) - Point (P		Diagonal Size	Measured	97.5	97.5	97.5
Parte Interception Interception Interception Interception		Resol	ution	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)
Parte Interception Interception Interception Interception		Brightne	ss (Typ.)	700 nit	500 nit	450 nit
Parte Here DB DB DB DB   1000000000000000000000000000000000000				Landscape/Portrait	Landscape/Portrait	
Panel Contract Rest (F)						
Image: Problem Probability	Panel					
Addre Briging weak emb 2.2000/01/2001/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000 2.2000/01/2000/01/2000/01/2000/01/2000 2.2000/01/2000						
Pearler Origination Origination Origination Origination   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation 300 Gamma 300 Gamma 300 Gamma 300 Gamma   Operation		Ty	pe	VA	VA	VA
Image: constraint of the second sec		Active Displa	y Area (mm)	2,158.85 (H) x 1,214.35 (V)	2,158.85 (H) x 1,214.35 (V)	2,158.85 (H) x 1,214.35 (V)
Operational of the set of the s		Pixel Pit	ch (mm)	0.562 x 0.562	0.562 x 0.562	0.562 x 0.562
Operational of the set of the s		Color (	Gamut	NTSC 72%	NTSC 72%	DCI 93%
Note of the second se						
Marcy /Sound Alloc UB2 / UB2 / U		operatio				
Image: constraint of the stand of						
Image: constraint of the second se		INPUT				
Vision 0 Vision 0			USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
Yound Definition VILLO MOTENT NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO USH NADO NADO NADO NADO NADO NADO NADO NADO	Connectivity		TUNER	N/A	N/A	N/A
VS000 PC QUIPUT B AUDO B Stemain Lak B			VIDEO	N/A	N/A	N/A
Image: bit mail fails in the state of the stat	/ Sound	OUTPUT				
Image: control Ensemption (control Percent (control)						
Image: second						
Immunof Precision Special Speci Special Speci Special Special Special Special Special Special						
		Spea	aker		10W 2ch	40 W x 2.2 CH
Percentage Percentage 2,201,139:420 2,201,139:420 2,201,139:420 2,201,139:420 2,201,139:420   Weight (a) Set <thset< th=""> Set <thset< th=""> Se</thset<></thset<>		Dimonsion (mm)	Set	2,193.2 x 1,248.8 x 48.1	2,193.2 x 1,248.8 x 48.1	2,180.6 x 1,243.9 x 48.4
Merght ID Special PC Special PC Special PC Special PC Special PC Special PC PC PC   VERSING VERSING PC VERSING PC Mont Surver (Minutation PC Mont		Diffiension (mm)	Package	2,370 x 1,395 x 230	2,370 x 1,395 x 230	2,379 x 1,431 x 350
Meeting is a set of the set of t						
Special Website Kext Mounit Sec: With Minute Beam With Minute Verter Minute V	Mechanical	Weight (kg)				
	Spec	1/504				
Beel Herei Hinn) 14.8 (Even) 14.8 (Even) 14.8 (Even) 14.8 (Even) 14.8 (Even)   Design Beek Internal Figure Hight						
Design Network Base Lot State Back State Back Inter Black   Image: State Disc, State				M8, 16~18mm	M8, 16~18mm	M8, 16~18mm
Preduces Idea Synaps-with Suit-Magicito S10, S25 P10 Idea Synaps-with No compability WM Magicitor Class VVT No compatibility		Bezel Wig	dth (mm)	14.8 (Even)	14.8 (Even)	3 bezeless
Presenter Internal Party Utb Signage with Built in Magicine Sign. </td <td>Design</td> <td>Bezel</td> <td>Color</td> <td>Slate Black</td> <td>Slate Black</td> <td>Titan Black</td>	Design	Bezel	Color	Slate Black	Slate Black	Titan Black
Features Processor Control (Call Science) Control (Call Science)   Special Processor Control (Call Science) Control (Call Science)   Special From (Call Science) Control (Call Science) Control (Call Science)   Special From (Call Science) Control (Call Science) Control (Call Science)   Special Special Special Control (Call Science) Control (Call Science)   Special Special Special Control (Call Science) Control (Call Science)   Special Special Special Contro (Call Science) Control (Call Science) </td <td>-</td> <td colspan="2">Key</td> <td>SSSP 10.0</td> <td>Built-in MagicInfo S10, SSSP 10.0</td> <td>MagicInfo Player S10 Lite</td>	-	Key		SSSP 10.0	Built-in MagicInfo S10, SSSP 10.0	MagicInfo Player S10 Lite
Features Processor CA31 363E Quad-Gree CA31 363E Quad-Gree Constrained processor   Features Storage (PDM) 16 GBI Quad-Gree 16 GBI QB available) 8 GBI GB available)   Features H/W Add Gen, B25 Beign 2/// Gen, B25 Beign 2/// Gen, B25 Beign 2/// Gen, B25 Beign   Special H/W Add Gen, B25 Beign 2/// Gen, B25 Beign Add Leel 2/// Gen, B25 Beign   Special H/W Add Beign 2//  Gen, B25 Beign Add Leel Center J2   Special Filt Signage New Yorne Add Leel Add Leel Center J2   Special Symage New Yorne Signage New Yorne Signage New Yorne Signage New Yorne   Symage Symage New Yorne Signage New Yorne Signage New Yorne Signage New Yorne   Symage Signage New Yorne Signage New Yorne Signage New Yorne Signage New Yorne   Symage Signage New Yorne Signage New Yorne Signage New Yorne Signage New Yorne   Symage Signage New Yorne Signage New Yorne Signage New Yorne Signage New Yorne			Operating System			
Features Storage (FDM) 16 GR0 (G available) 16 GR0 (G available)   Features Arrow (G available) 2nd (G available) 2nd (G available)   Features Arrow (G available) 2nd (G available) 2nd (G available)   Special Arrow (G available) 2nd (G available) 2nd (G available)   Special Features Arrow (G available) 2nd (G available)   Special Special Special Special 2nd (G available)   Special Special Special Special Special Special 2nd (G available)   Special Special Special Special Special Special 2nd (G available)   Special Special Special Special Special Special 2nd (G available)   Special Special Special Special Special Special 2nd (G available)   Special Special Special Special Special Special 2nd (G available)   Special Special Special Special						Cortex A7217GHz Quad-Core
Features Image: Special Image: Specia						
Features k-/W L (Cuber R) Cuber R)	Features		Storage (LDM)			8 GB(3 GB available)
Special Special Signage-New Home (Signage-New Home Custom Home Auto Source's Witching & Recovery Dicon Simulation Mode Diction Simulation Mode Diction Mode			H/W	Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2.4/5.061zdual) & BT	Center IR Temperature Sensor Ambient Sensor Auto Level Wi-Fi(2 4/5 OGHz dual) & BT	Center IR Temperature Sensor Auto Level
ertification $                                    $		Special	S/W	Signage New Home Workspace (Microsoft 36/VMware/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode SIMARTVIEW+ Upgradable Web-Engine	Signage New Home Workspace (Microsoft 365/V/Mware/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode SMARTVIEW+ Upgradable Web-Engine	Auto Source Switching & Recovery HDR support
EnvironmentEnvironmentEPEATEPEATEPEATIP Retring to the probability of the p				Smart Calibration HDR support	Smart Calibration HDR support	
$\begin{tabular}{ c                                   $				Smart Calibration HDR support 60950-1 / 62368-1	Smart Calibration HDR support 60950-1/62368-1	
Image: Part of the state o				Smart Calibration HDR support 60950-1 / 62368-1	Smart Calibration HDR support 60950-1/62368-1	
Note Noe Note Note <th< td=""><td>ortification</td><td>EM</td><td>1C</td><td>Smart Calibration HDR support 60950-1/62368-1 Class A</td><td>Smart Calibration HDR support 60950-1 / 62368-1 Class A</td><td>Class B</td></th<>	ortification	EM	1C	Smart Calibration HDR support 60950-1/62368-1 Class A	Smart Calibration HDR support 60950-1 / 62368-1 Class A	Class B
Power Max[W/h] AC100-240 V,50/60Hz AC100-240 V,50/60Hz AC100-240 V,50/60Hz   Power Max[W/h] 517 363 275   Typical[W/h] Gamma 6000000000000000000000000000000000000	Certification	EM Enviror	1C nment	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT	Class B EPEAT
Power Consumption Max[W/h] 517 363 275   Typical[W/h] Typical[W/h] 700 197 197   Operating Condition Temp=tum Generation 188 188 188   Operating Condition Temp=tum 0°C-40°C 0°C-40°C 0°C-40°C   Operating Condition Temp=tum 0°C-40°C 0°C-40°C 0°C-80°K   Inclusion Quick Setup Guide, Warranty Card, Power Cord RS232C(IN) Gender REB322C(IN) Ge	Certification	EM Enviror IP Ra	nment ting	Smart Calibration HDR support 60950-1/63268-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP	Class B EPEAT N/A 802.1x(WPA2 Enterprise): EAP-TLS, EAP-PEAP
$\begin{array}{ c c c c } \hline Power \\ \hline Power \\ \hline Consumption \\ \hline Consumpti$	Certification	EM Environ IP Ra Secu	1C nment ting urity	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 8023.tx(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal	Smart Calibration HOR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP WPA3-Personal	Class B EPEAT N/A 802.tx(WPA2Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal
Consumption Typical(W/h) Gase Typical(W/h) Gase Typical(W/h) Gase Typical(W/h) Gase Typical(W/h) Gase Typical(W/h) Gase	ertification	EM Environ IP Ra Secu	IC nment ting supply	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1%(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TIS_5, EAP-TITLS_ EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz	Class B EPEAT N/A 802.1x(WPA2Enterprise): EAP-TILS, EAP-TILS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz
Sleep mode Sleep mode less than 0.5W less than 0.5W   Operating Temp=rature 0°C-40°C 0°C-40°C   Condition Relative + umidity 0°C-40°C 0°C-40°C   Marrianty 10-80% 0°C-40°C 0°C-40°C   Incluity 0°C-40°C 0°C-40°C 0°C-40°C   Version Relative + umidity 0°C-40°C 0°C-40°C   Version Name 0°C-40°C 0°C-40°C   Version Paratiny 0°C-40°C 0°C-40°C   Version Quick Setup Guide, Warranty Card, Power Cord RES232C(IN) Gender RES232C(IN) Gender REMOTE Controller & Batteries Peremote Controller & Batteries   NA NAA NAA In Box   Optional Mount WMN-8200SC WMN-8200SC		EM Enviroi IP Ra Secu Power !	IC nment ting urity Supply Max[W/h]	Smart Calibration HDR support 60950-1 / 62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 517	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-TEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 363	Class B EPEAT N/A 802.11(WPA2Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240V, 50/60 Hz 275
Condition Relative Humidity 10-80% 10-80%   Condition Relative Humidity 0.0-80% 0.0-80%   Locessories LincLues Quick Setup Guide, Warranty Card, Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries   Mount Stand Mount N/A N/A In Box		EM Enviro IP Ra Secu Power !	IC nment ting urity Supply Max[W/h] Typical[W/h]	Smart Calibration HDR support 60950-1/ 62368-1 Class A EPEAT IP5x 8021:tt(WPA2 Interprise): EAP-TLS, EAP-TTLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 517 270	Smart Calibration HDR support 60950-1/62568-1 Class A EPEAT IP5x 802.1%(PM2E Interprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197	Class B EPEAT N/A 802.1tt(VPA2Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240V, 50/60 Hz 275
Condition Relative Humidity 10-80% 10-80%   Condition Relative Humidity 0.0-80% 0.0-80%   Locessories LincLues Quick Setup Guide, Warranty Card, Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries Quick Setup Guide, Warranty Card, Power Cord Power Cord RSZ32C(IN) Gender Remote Controller & Batteries   Mount Stand Mount N/A N/A In Box		EM Enviro IP Ra Secu Power !	IC nment ting urity Supply Max[W/h] Typical[W/h]	Smart Calibration HDR support 60950-1/ 62368-1 Class A EPEAT IP5x 8021:tt(WPA2 Interprise): EAP-TLS, EAP-TTLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 517 270	Smart Calibration HDR support 60950-1/62568-1 Class A EPEAT IP5x 802.1%(PM2E Interprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197	Class B EPEAT N/A 80021(WIPAZ Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP WPA3-Personal AC100 - 240V, 50/60 Hz 275 197
VCCESSORIEs Stand Quick Setup Guide, Warranty Card, Power Cord Quick Setup Guide, Power Cord Quick Setup G	Power	EM Environ IP Ra Secu Power Consumption	IC nment ting supply Max[W/h] Typical[W/h] Sleep mode	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 8021:tk(WPAZ Interprise): EAP-TLS, EAP-TTLS, EAP-PEAP WPA3-Personal AC100-240 V, 50/60 Hz 517 270 Less than 0.5W	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TES, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 Less than 0.5W	Class B EPEAT N/A 802.1xt/WPA2 Enterprise): EAP-TLS, EAP-TES, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 275 197 less than 0.5W
Stand Stand N/A N/A In Box   Optional Mount WMN-8200SC WMN-8200SC WMN-8200SC	Power Operating	EM Environ IP Ra Sect Power ! Consumption Tempe	IC nment ting urity Supply Max[W/h] Typical[W/h] Sleep mode rature	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 517 270 Less than 0.5W 0°C~ 40°C	Smart Calibration HOR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TTL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 Less than 0.5W 0°C- 40°C	Class B EPEAT N/A 802.1xt(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 275 197 less than 0.5W 0°C~ 40°C
Optional Mount WMN-8200SC <td>Operating Condition</td> <td>EM Enviro IP Ra Secu Power Consumption Tempe Relative H</td> <td>IC mment ting Supply Max[W/h] Typical[W/h] Sleep mode ature Humidity</td> <td>Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 517 270 less than 0.5W 0°C~ 40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5325(UK) Gender</td> <td>Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TTL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 Less than 0.5W 0°C-40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5232(LIN) Gender</td> <td>Class B EPEAT N/A 802.1%(VPA2Enterprise): EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 275 197 Less than 0.5W 0°C-40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5232(CII) Gender</td>	Operating Condition	EM Enviro IP Ra Secu Power Consumption Tempe Relative H	IC mment ting Supply Max[W/h] Typical[W/h] Sleep mode ature Humidity	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 517 270 less than 0.5W 0°C~ 40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5325(UK) Gender	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TTL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 Less than 0.5W 0°C-40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5232(LIN) Gender	Class B EPEAT N/A 802.1%(VPA2Enterprise): EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 275 197 Less than 0.5W 0°C-40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord R5232(CII) Gender
	Power Operating Condition	EM Enviro IP Ra Secu Power Consumption Tempe Relative H	IC Inment ting Virity Supply Max[W/h] Typical[W/h] Sleep mode rature Humidity ded	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1%(WPA2 Enterprise): EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 517 270 Less than 0.5W 0.0°C - 40°C 10-80% Quick Setup Guide, Warranty Card, Power Cord RS232C(IN) Gender Remote Controller & Batteries	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TTL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 less than 0.5W 0°C-40°C 10-80% Quick Setup Guide, Warrany Card, Power Cord Power Cord RS232C(IN) Gender Remote Controller & Batteries	Class B EPEAT N/A 802.1%(VPA2Enterprise): EAP-TLS, EAP-TLS, EAP-TLS, EAP-TLS, EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240V, 50/60Hz 275 197 less than 0.5W 0°C - 40°C 10-80% Quick Setup Guide, Warrany Card, Power Cord, Power Cord, RSZ52C(IN) Gender Remote Controller & Batteries
	Power Operating	EM Environ IP Ra Secc Power Consumption Tempe Relative H Inclu	IC nment ting Supply Max[W/h] Typical[W/h] Sleep mode rature Humidity ded Stand	Smart Calibration HDR support 60950-1 / 62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 517 270 Less than 0.5W 0°C- 40°C 10-80% Quick Setup Guide, Warranty Card, POwer Cord Ress223C(IN) Gender Remote Controller & Batteries N/A	Smart Calibration HDR support 60950-1/62368-1 Class A EPEAT IP5x 802.1x(WPA2 Enterprise): EAP-TL5, EAP-TL5, EAP-PEAP WPA3-Personal AC 100 - 240 V, 50/60 Hz 363 197 less than 0.5W 0°C - 40°C 10-80% Quick Setup Guide, Warranty Card, POwer Cord RES232C(IN) Gender Remote Controller & Batteries N/A	Class B EPEAT N/A 802.1%(PAZ Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP WPA3-Personal AC100 - 240 V, 50/60 Hz 275 197 Less than 0.5W 0°C - 40°C 10-80% Quick Setup Guide, Warranty Card, POwer Cord RS232C(IN) Gender Remote Contoller & Batteries In Box

#### About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. Inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

#### Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2024 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677 Republic of Korea

2024-07